



Product Specification Data



Description

Rad Grafix Vinyl, the industry's leading choice for printable, wall graphic material in its class. It is a tough, durable, polymeric plastic film. Rad Grafix Vinyl is abrasion resistant, and exhibits resistance to oils, chemicals, and some solvents. Rad Grafix Vinyl is an excellent choice for repositionable wall graphics, appliques, Point-of-Purchase solutions, or temporary outdoor signage.

Applications

Rad Grafix Vinyl is ideal for wall graphics, floor decals, posters, labels and stickers. Full bleed printing is not a problem with this film. This film can be removed without damage to the wall for up to one year.

Adhesion

Rad Grafix Vinyl has a repositionable adhesive that has a clean removability up to one year. It is always suggested to test the adhesion to the wall if the wall has recently been painted.

Thickness

Film	6 mil
Adhesive	.8 to 1.2 mil
Liner	7 mil
(Thickness variance \pm 10%)	

Removability

Removable up to 1 year under normal interior exposure conditions and applications.

Dimensional Stability

Good

Temperature Ranges

Minimum application temperature is 40°F.
Service temperature range is 20°F to 200°F.

Liner

Heavyweight, bleached kraft, poly-coated on both sides

Storage Stability

1 year shelf life when stored at 70°F and 50% relative humidity.

Product Series

RADV54150	54" x 150'
RADV5430	54" x 30'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.